



# TECHNICAL DATA SHEET

## AD-Tec 35 15W-40

5 Litre & 199 Litre

### Product Description

AD-TEC 35 15W-40 is a high quality mineral engine oil formulated with a balanced blend of quality base oil and additives to produce a lubricant that offers an excellent level of engine protection with outstanding cleanliness. AD-TEC 35 can be used in petrol & diesel engines both turbo and naturally aspirated.

### Recommended for use by AD for the following manufacturer's specifications


ACEA: A3/B4

API: SN/CF

MB: 229.1 & 229.3

Volvo: VDS-2

VW: 505.00 & 505.01



Size	Part No	Barcode
5 Litre	AZD005	5020618202431
199 Litre	AZD199	5020618202998

### Product Benefits

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Suitable for petrol and diesel engines
- \* Outstanding engine cleanliness and sludge control

### Product Usage

For engines where this specification lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Store upright and sealed in a cool, dry place out of the reach of children.

Revision: 1 | Date: 27/04/2022



# TECHNICAL DATA SHEET

## AD-Tec 35 15W-40

5 Litre & 199 Litre

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Base Oil	:	More Than 70%
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	14.05
Viscosity, CCS -20°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		10.62
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	
Pour Point	ASTM D97	°C		-25	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			104.34
Density	ASTM D792	@ 15°C			0.889

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 27/04/2022