

## AD-Tec 44 5W-30

20 Litre

### Product Description

AD-TEC 44 5W-30 is a semi synthetic engine oil designed to provide maximum protection for modern engines requiring a low viscosity oil. It is suitable for lean burn, multi-valve, injection, twin cam, turbo charged and early model Ford Zetec engines.

### Recommended for use by AD for the following manufacturer's specifications

ACEA: A5/B5

API: SL/CF

### Product Benefits

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection



\* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	AAG020	5020618202455

### Product Usage

For engines where this specification lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Store upright and sealed in a cool, dry place out of the reach of children.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Base Oil	:	More Than 80%
Percentage of Biodiesel	:	Nil

Revision: 1 | Date: 27/04/2022

### IMTFA Ltd

PO Box 335, Par, Cornwall, PL25 9HH

Email: info@imtfa.co.uk

To find the recommended oil for your vehicle please visit **[www.adoil.co.uk](http://www.adoil.co.uk)** or speak directly to one of our stockists.



## AD-Tec 44 5W-30

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.9
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°c		-27	
NOACK Volatility	ASTM D5800	%		13	
Total Base Number	ASTM D2896	mg KOH/g	10		12.1
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			66.4
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				156
HTHS Viscosity	ASTM D4683	mPa.s	3	3.5	

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.