

TECHNICAL DATA SHEET

AD-Tec 44 5W-30

20 Litre

Product Description

AD-TEC 44 5W-30 is a semi synthetic engine oil designed to provide maximum protection for modern engines requiring a low viscosity oil. It is suitable for lean burn, multi-valve, injection, twin cam, turbo charged and early model Ford Zetec engines.

Recommended for use by AD for the following manufacturer's specifications

ACEA: A5/B5 API: SL/CF

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	AAG020	5020618202455

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store upright and sealed in a cool, dry place out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Base Oil : More Than 80%

Percentage of Biodiesel : Nil Revision: 1 | Date: 27/04/2022



TECHNICAL DATA SHEET

AD-Tec 44 5W-30

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	10.9
Viscosity, CCS -30°c	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°c		-27	
NOACK Volatility	ASTM D5800	%		13	
Total Base Number	ASTM D2896	mg KOH/g	10		12.1
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			66.4
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				156
HTHS Viscosity	ASTM D4683	mPa.s	3	3.5	

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.