

TECHNICAL DATA SHEET

AD-Tec 3 0W-20 VW

5 Litre, 20 Litre & 199 Litre

Product Description

AD-TEC 0W/20 VW is specially formulated low viscosity fully synthetic engine oil to match the oil test requirements of VW 508.00/509.00. It provides enhanced engine protection against component wear and is safe for use in vehicles that have Diesel Particulate Filters (DPF) and gasoline Particulate Filers as well as Catalytic convertors.

Please note - this oil is not backwards compatible to other VW specifications and it contains a coloured dye for identification.

Recommended for use by AD for the following manufacturer's specifications

Porsche: C20

VW: 508.00 & 509.00

Product Benefits

- *Fully synthetic low viscosity fuel efficient engine oil
- *Ideal for petrol and diesel engines
- *Low Viscosity, fuel efficient

* Image for illustrative purposes only. Size Part No Barcode 5 Litre AGB005 5020618203100 20 Litre AGB020 5020618202783

AGB199

5020618202943

199 Litre

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance : Pale Green Liquid

Odour : Characteristic

Solubility : Insoluble in water Revision: 1 | Date: 17/01/2023



TECHNICAL DATA SHEET

AD-Tec 3 0W-20 VW

5 Litre, 20 Litre & 199 Litre

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	7.8	<9.3	8.7
Viscosity, CCS -35°c	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		8.33
HTHS Viscosity	ASTM D4683	mPa.s	2.6	<2.9	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			42.74
Density	ASTM D792	@ 15°c			0.841

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 17/01/2023