

TECHNICAL DATA SHEET

AD-Tec 9 0W/30 C3

20 Litre & 199 Litre

Product Description

AD-Tec 9 0W-30 C3 is the very latest generation fully synthetic low viscosity engine oil. AD-Tec 9 0W-30 C3 offers excellent fuel efficiency and engine protection whilst meeting the requirements of soot control for those vehicles with engine exhaust after treatment devices fitted.

Recommended for use by AD for the following manufacturer's specifications

ACEA: C3 API: SN BMW: LL-04 MB: 229.51 Porsche: C30

VW: 503.00, 504.00, 506.00, 506.01 & 507.00



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	ATK020	5020618202899
199 Litre	ATK199	5020618202905

Product Benefits

- * Low SAPS formulation
- * Fully synthetic
- * Excellent fuel efficiency

Product Usage

For vehicles where this grade and specification of engine oil is required.

Directions for Use

Use as specified by the vehicle manufacturer

Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children.

Shelf Life

5 years from date of manufacture

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water Revision: 1 | Date: 11/03/2024



TECHNICAL DATA SHEET

AD-Tec 9 0W/30 C3

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°c	ASTM D445	mm²/s	9.3	<12.5	11.3
Cold Cranking Viscosity	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		8.21
Pour Point	ASTM D97	°c		-42	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Kinematic Viscosity at 40°c	ASTM D445	mm²/s			59.17
Density	ASTM D792	@ 15°c			0.841

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 11/03/2024