



# TECHNICAL DATA SHEET

## AD-Tec 37 20W/50

199 Litre

### Product Description

AD-TEC 37 20W-50 is formulated to meet the requirements of older/high mileage vehicles where this specification of oil is recommended.

### Recommended for use by AD for the following manufacturer's specifications

API: SE/CC

### Product Benefits

- \* Ensures lubricant performance
- \* Suitable for petrol and diesel engines

### Product Usage

For engines where this lubricant specification is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Keep sealed in a cool, dry place.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water



\* Image for illustrative purposes only.

Size	Part No	Barcode
199 Litre	ACF199	5020618203001

Revision: 1 | Date: 11/03/2024



# TECHNICAL DATA SHEET

## AD-Tec 37 20W/50

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	16.3	<21.9	19.66
Viscosity, CCS -15°C	ASTM D4684	mPa.s		9500	
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			181.7
Density	ASTM D792	@ 15°C			0.882
Total Base Number	ASTM D2896	mg KOH/g			7.98

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 11/03/2024