

AD-Tec 18 5W/30 DX

20 Litre

Product Description

AD-Tec 18 5W-30 DX is a high performance fully synthetic engine oil that provides protection against low speed pre-ignition (LSPI) issues associated with smaller capacity turbocharged engines. AD-Tec 18 5W-30 DX is suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

Recommended for use by AD for the following manufacturer's specifications

API: SN, SN Plus, SN-RC, SP & SP-RC

Chrysler: MS-6395

GM: 4718M, 6094M, Dexos™ 1 Gen 2 & Dexos™ 1 Gen 3

Honda: HTO-06

ILSAC: GF-5 & GF-6A



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	AGX020	5020618202936

Product Benefits

- * Helps resolve LSPI issues
- * Fuel Efficient
- * Fully Synthetic

Directions for Use

Use as per manufacturer's recommendations

Storage Instructions

Store upright in a cool dry place out of the reach of children

Shelf Life

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Flammability	:	Non Flammable
Percentage of Biodiesel	:	Nil

Revision: 1 | Date: 11/03/2024

IMTFA Ltd

PO Box 335, Par, Cornwall, PL25 9HH

Email: info@imtfa.co.uk

To find the recommended oil for your vehicle please visit **www.adoil.co.uk** or speak directly to one of our stockists.



AD-Tec 18 5W/30 DX

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.4
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		10.9
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			63.3
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				145

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.